

TATA SOLAR PLATINUM™



India's best solar photovoltaic modules for specialty applications



Premium quality modules manufactured by Tata in India for over 20 years



Rugged and durable design enabling easy installation and long life



Leading edge equipment plus world class processes from BP Solar



Greater power output in limited spaces by using high efficiency cells



Greater energy generated due to positive power tolerance of up to 10%



Peace of mind guaranteed with Tata Power Solar 25 year module power warranty



PRODUCT FEATURES

- High power output using high efficiency cells and ultra-clear solar glass
- UV resistant, weather-proof junction boxes with bypass diodes
- Torsion and corrosion resistance with anodized screw type aluminium frame
- Higher impact resistance using scratch resistant toughened solar glass
- RF enabled module tracking and identification

APPLICATIONS

- Lighting: lanterns, indoor and street
- Telecommunication and radio relay stations
- Stand alone systems / telemetry systems
- Defence and offshore requirements
- Signage and outdoor media
- Mobile chargers / outdoor activities

SPECIFICATIONS

- Multiple configurations (36, 48 and 72 cells)
- Multiple wattages (5 to 190Wp)
- Mono and multi-crystalline cells (125mm and 156mm)
- IV curve and specifications available for all products
- RFID included

Modules in the Platinum series	Platinum				
	10	37	74	100	150

Electrical parameters at standard test conditions (STC)*

	10	37	74	100	150
Nominal power output (W)	10	37	74	100	150
Power tolerance (%)	0 ~ +10	0 ~ +10	0 ~ +10	0 ~ +10	0 ~ +10
Voltage at P _{MAX} V _{MPP} (V)	18.2	18.0	18.0	18.2	18.2
Current at P _{MAX} I _{MPP} (A)	0.55	2.05	4.12	5.50	8.28
Open-circuit voltage Voc (V)	21.8	21.8	21.8	22.1	22.5
Short-circuit current I _{SC} (A)	0.60	2.23	4.45	6.02	8.64

Module general characteristics

Number of cells	36	36	36	36	36
Length (mm)	293	481	831	1098	1501
Width (mm)	337	660	660	660	660
Thickness (mm)	17	38.5	38.5	38.5	38.5
Weight (kg)	1.2	3.8	6.3	8.5	12.0
Frame material	Silver anodized aluminium				
Superstrate	3.2 mm glass				
Substrate	PET				
Encapsulant	EVA				

Environment and operating conditions

Operating temperature range (°C)	-40 and +85
----------------------------------	-------------

Warranty

Product warranty (years)	5
Power output warranty (years)	10 (90% of rated power output) 25 (80% of rated power output)

Wide range of Tata Solar Platinum series modules include the following: 5, 6, 10, 12, 18, 20, 24, 37, 65, 74, 80, 100, 125, 150 and 190 Wp.

Applications



Stand alone systems for homes with no grid connectivity



Indoor and outdoor lighting



Power packs for remote telecom sites and telemetry stations



Street lighting and community lighting



Offshore installations and hazardous locations



Lighting billboards and outdoor media



Portable mobile phone chargers

YOUR LOCAL DEALER

Tata Power Solar is committed to enabling solar everywhere and bringing the power of the sun to people in the most efficient and cost effective way possible.



For sales, service and other enquiries, email us modules.solar@tatapower.com

www.tatapowersolar.com

* Irradiance of 1000W/m², spectrum AM of 1.5 and cell temperature of 25°C
Best in class AAA solar simulator (IEC 60904-9) used, power measurement tolerance ±3%

Listed specifications are subject to change without notice